

EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



EN 3033-5:2021

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



Smederevac

O nama About company	2
Štednjaci na čvrsto gorivo Solid fuel cookers	3 - 20
Peći na čvrsto gorivo Solid fuel stoves	21 - 40
Štednjaci i peći za etažno grejanje Central heating cookers and stoves	43 - 52
Peći, štednjaci i kotlovi na pellet Pellet stoves, cookers and boilers	53 - 60
Električni stoni štednjak Electric tabletop cooker	61 - 62
Tabela tehničkih karakteristika Technical data table	63 - 72

O nama

Kompanija Smederevac d.o.o. iz Smedereva osnovana je 1923. godine i predstavlja jedan od najprepoznatljivijih brendova u oblasti proizvodnje šporeta i peći na čvrsta goriva, kao i kotlova i peći na pelet. Kroz istoriju i rast naše kompanije ostvarene su saradnje sa francusko-belgijskom firmom ARTUR-MARTIN, korporacijom CANDY, HOOVER, ROSIERES, ZERO WATT, IBERNA, KELVINATOR, OTSEIN i GASFIRE.

Sa više od jednog veka kontinuiranog rada i iskustva, Smederevac je simbol pouzdanosti, trajnosti i domaće topline, prisutan u domovima širom Evrope i sveta. Na temeljima bogate tradicije gradimo savremena rešenja za grejanje i kuvanje, oslanjajući se na spoj proverenog znanja i moderne tehnologije. Kontinuirano ulažemo u razvoj, unapređenje proizvodnih procesa i kontrolu kvaliteta. Naši proizvodi projektovani su sa posebnim fokusom na funkcionalnost, dug vek trajanja, energetska efikasnost i ekološke standarde, kako bi odgovorili na potrebe savremenog domaćinstva i zahtevnih tržišta.

Sa tendencijom rasta i osvajanja što većeg broja tržišta idemo u korak sa potrebnim standardima i sertifikatima, pa tako 1998. godine dobijamo nacionalni sertifikat za sistem kvaliteta usaglašen sa zahtevima standarda JUS ISO 9001, a 2003. godine i sertifikat od strane TÜV CERT za integrisani sistem kvaliteta i zaštite životne sredine usaglašen sa zahtevima standarda ISO 9001:2015 i 14001:2015.

Od tog perioda pa sve do danas, nadzornim proverama i resertifikacijama, nastavlja da potvrđuje svoju opredeljenost ka zadovoljenju potreba i zahteva kupaca kroz negovanje savremenih tokova poslovanja i obezbeđenje propisanih uslova zaštite životne sredine.

Smederevac nije samo naziv proizvoda - to je garancija kvaliteta, tradicije i poverenja koje traje generacijama.

About company

The company Smederevac d.o.o. from Smederevo was founded in 1923 and represents one of the most recognizable brands in the field of solid fuel stoves and stoves, as well as boilers and pellet stoves. Throughout the history and growth of our company, collaborations have been achieved with the French-Belgian company ARTHUR-MARTIN, the corporation CANDY, HOOVER, ROSIERES, ZERO WATT, IBERNA, KELVINATOR, OTSEIN and GASFIRE.

With more than a century of continuous work and experience, Smederevac is a symbol of reliability, durability and domestic warmth, present in homes throughout Europe and the world. On the foundations of a rich tradition, we build modern solutions for heating and cooking, relying on a combination of proven knowledge and modern technology. We continuously invest in development, improvement of production processes and quality control. Our products are designed with a special focus on functionality, long life, energy efficiency and environmental standards, in order to meet the needs of modern households and demanding markets.

With the tendency to grow and conquer as many markets as possible, we keep up with the necessary standards and certificates, so in 1998 we received a national certificate for the quality system in accordance with the requirements of the JUS ISO 9001 standard, and in 2003 a certificate from TÜV CERT for the integrated quality and environmental protection system in accordance with the requirements of the ISO 9001:2015 and 14001:2015 standards. From that period until today, through supervisory checks and certifications, continues to confirm its commitment to meeting needs and demands customers through nurturing modern business processes and security prescribed environmental protection conditions.

Smederevac is not just the name of the product - it is a guarantee of quality, tradition and trust that lasts for generations.

Štednjaci na čvrsto gorivo

Solid fuel cookers



SD 3

Dimenzije (VxŠxD)	740x720x570 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	195x200x300 mm
Firebox dimensions (HxWxD)	
Dimenzije pečnice (VxŠxD)	200x300x400 mm
Oven dimensions (HxWxD)	
Snaga	7 kW
Power	
Stepen iskorišćenja	75 %
Efficiency	
Odvod dima	sa strane /
Fume outlet	side / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





SD 7 SL

Dimenzije (VxŠxD)	710x816x580 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	250x200x420 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	200x433x463 mm
Oven dimensions (HxWxD)	
Snaga	7 kW
Power	
Stepen iskorišćenja (drvo)	75 %
Efficiency	
Odvod dima	sa strane /
Fume outlet	side / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



SD 7 RS

Dimenzije (VxŠxD)	710x816x580 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	250x200x420 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	200x433x463 mm
Oven dimensions (HxWxD)	
Snaga	7 kW
Power	
Stepen iskorišćenja	75 %
Efficiency	
Odvod dima	sa strane /
Fume outlet	side / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





ŠTEDNJACI NA ČVRSTO GORIVO
SOLID FUEL COOKERS

SD 9 SL

Dimenzije (VxŠxD)	710x944x580 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	250x200x420 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	200x490x460 mm
Oven dimensions (HxWxD)	
Snaga	7 kW
Power	
Stepen iskorišćenja	75 %
Efficiency	
Odvod dima	sa strane /
Fume outlet	side / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



SD 9 RS

Dimenzije (VxŠxD)	710x944x580 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	250x200x420 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	200x490x460 mm
Oven dimensions (HxWxD)	
Snaga	7 kW
Power	
Stepen iskorišćenja	75 %
Efficiency	
Odvod dima	sa strane /
Fume outlet	side / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ŠTEDNJACI NA ČVRSTO GORIVO
SOLID FUEL COOKERS

SD 10

Dimenzije (VxŠxD)	850x945x585 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	250x200x420 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	200x490x460 mm
Oven dimensions (HxWxD)	
Snaga (drvo)	7 kW
Power (wood)	
Stepen iskorišćenja (drvo)	75 %
Efficiency (wood)	
Odvod dima	sa strane, gore /
Fume outlet	side, top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

TREND NEW LINE

Dimenzije (VxŠxD)	855x893x493 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	256x282x342 mm
Firebox dimensions (HxWxD)	
Dimenzije pečnice (VxŠxD)	205x367x333 mm
Oven dimensions (HxWxD)	
Snaga	7,1 kW
Power	
Stepen iskorišćenja	76,3 %
Efficiency	
Odvod dima	sa strane /
Fume outlet	side / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ŠTEDNJACI NA ČVRSTO GORIVO
SOLID FUEL COOKERS

ROYAL 720 2.0

Dimenzije (VxŠxD)	850x720x600 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	216x200x365 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga	6,5 kW
Power	
Stepen iskorišćenja	83,6 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

KING

Dimenzije (VxŠxD)	860 - 900x810x600 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	310x197x350 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga (drvo)	7,8 kW
Power (wood)	
Stepen iskorišćenja (drvo)	75,4 %
Efficiency (wood)	
Odvod dima	sa strane, gore, pozadi /
Fume outlet	side, top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ŠTEDNJACI NA ČVRSTO GORIVO SOLID FUEL COOKERS

ARES

Dimenzije (VxŠxD)	860-900x810x600 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	300x197x385 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga (drvo)	7,37 kW
Power	
Stepen iskorišćenja (drvo)	78,4 %
Efficiency	
Odvod dima	sa strane, gore /
Fume outlet	side, top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

ARES LUX

Dimenzije (VxŠxD)	860-900x810x600 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	300x197x385 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga (drvo)	7,37 kW
Power	
Stepen iskorišćenja (drvo)	78,4 %
Efficiency	
Odvod dima	sa strane, gore /
Fume outlet	side, top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ŠTEDNJACI NA ČVRSTO GORIVO SOLID FUEL COOKERS

AS II

Dimenzije (VxŠxD)	845x900x654 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	270x270x350 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga	9,9 kW
Power	
Stepen iskorišćenja (drvo)	82 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

AS II S

Dimenzije (VxŠxD)	845x900x654 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	270x270x350 mm
Firebox dimensions (HxWxD)	
Dimenzije pečnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga	9,9 kW
Power	
Stepen iskorišćenja	82 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood





EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ŠTEDNJACI NA ČVRSTO GORIVO
SOLID FUEL COOKERS

MAGNUM II

Dimenzije (VxŠxD)	850x1070x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	300x250x340 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga	7,75 kW
Power	
Stepen iskorišćenja	83,8 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

MAGNUM II S

Dimenzije (VxŠxD)	850x1070x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	300x250x340 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga	7,75 kW
Power	
Stepen iskorišćenja	83,8 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood





EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ŠTEDNJACI NA ČVRSTO GORIVO
SOLID FUEL COOKERS

GRAND 90

Dimenzije (VxŠxD)	870-900x900x600 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	250x210x456 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	248x302x420 mm
Oven dimensions (HxWxD)	
Snaga (drvo)	7 kW
Power	
Stepen iskorišćenja (drvo)	73,2 %
Efficiency	
Odvod dima	sa strane, gore, pozadi /
Fume outlet	side, top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

STRONG II

Dimenzije (VxŠxD)	865x915x655 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	195x200x400 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	440x300x445 mm
Oven dimensions (HxWxD)	
Snaga	7,6 kW
Power	
Stepen iskorišćenja	76,5 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 / 130 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



Peći na čvrsto gorivo

Solid fuel stoves



SD HAPPY ECO

Dimenzije (VxŠxD)	712x400x406 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	247x282x293 mm
Firebox dimensions (HxWxD)	
Snaga	5,7 kW
Power	
Stepen iskorišćenja	80,9 %
Efficiency	
Odvod dima	gore / top / Ø 120 mm
Fume outlet	
Tip goriva	drvo
Fuel type	wood

Boje
Colors



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025





SD HERA

Dimenzije (VxŠxD)	850x400x560 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	350x290x300 mm
Firebox dimensions (HxWxD)	
Snaga	6,2 kW
Power	
Stepen iskorišćenja	76,4 %
Efficiency	
Odvod dima	gore /
Fume outlet	top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

SD HIT ECO

Dimenzije (VxŠxD)	850x504x440 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	260x252x290 mm
Firebox dimensions (HxWxD)	
Snaga	6,4 kW
Power	
Stepen iskorišćenja	81,6 %
Efficiency	
Odvod dima	gore / top /
Fume outlet	Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors



SD CORNER ECO

Dimenzije (VxŠxD)	850x635x575 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	260x252x290 mm
Firebox dimensions (HxWxD)	
Snaga	6,3 kW
Power	
Stepen iskorišćenja	78 %
Efficiency	
Odvod dima	gore / top /
Fume outlet	Ø 120 mm
Tip goriva	drvo
Fuel type	wood



LUNA

Dimenzije (VxŠxD)	989x518x410 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	265x320x279 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	6 kW
Power (wood)	
Stepen iskorišćenja (drvo)	80 %
Efficiency (wood)	
Odvod dima	gore / top /
Fume outlet	Ø 150 mm
Tip goriva	drvo
Fuel type	wood





EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



PEĆI NA ČVRSTO GORIVO
SOLID FUEL STOVES

ORION

Dimenzije (VxŠxD)	1010x518x411 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	265x320x279 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	6 kW
Power (wood)	
Stepen iskorišćenja (drvo)	80 %
Efficiency (wood)	
Odvod dima	gore /
Fume outlet	top / Ø 150 mm
Tip goriva	drvo
Fuel type	wood

VEGA

Dimenzije (VxŠxD)	1044x493x431 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	293x335x310 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	6,4 kW
Power (wood)	
Stepen iskorišćenja (drvo)	80 %
Efficiency (wood)	
Odvod dima	gore /
Fume outlet	top / Ø 150 mm
Tip goriva	drvo
Fuel type	wood

Boje kamena
Stone colors





SD VESTA ECO

Dimenzije (VxŠxD)	890x455x440 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	400x280x340 mm
Firebox dimensions (HxWxD)	
Snaga	8,2 kW
Power	
Stepen iskorišćenja	77,8 %
Efficiency	
Odvod dima	gore / top /
Fume outlet	Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

VESTA PLUS II

Dimenzije (VxŠxD)	940x455x440 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	390x250x350 mm
Firebox dimensions (HxWxD)	
Snaga	7,5 kW
Power	
Stepen iskorišćenja	85,1 %
Efficiency	
Odvod dima	gore / top / Ø 120 mm
Fume outlet	
Tip goriva	drvo
Fuel type	wood

Boje
Colors



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025





PEĆI NA ČVRSTO GORIVO SOLID FUEL STOVES

ELIT II

Dimenzije (VxŠxD)	985x588x493 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	298x400x364 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	7,8 kW
Power (wood)	
Stepen iskorišćenja (drvo)	85,1 %
Efficiency (wood)	
Odvod dima	gore /
Fume outlet	top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

ARIA

Dimenzije (VxŠxD)	845x434x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	414x250x340 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	8 kW
Power (wood)	
Stepen iskorišćenja (drvo)	77 %
Efficiency (wood)	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





ARIA LUX

Dimenzije (VxŠxD)	845x434x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	414x250x340 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	8 kW
Power (wood)	
Stepen iskorišćenja (drvo)	77 %
Efficiency (wood)	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



Boje
Colors

GRAND 50

Dimenzije (VxŠxD)	860-900x515x573 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	256x381x375 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	7 kW
Power (wood)	
Stepen iskorišćenja (drvo)	76,3 %
Efficiency (wood)	
Odvod dima	gore / top /
Fume outlet	Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



OLYMP II

Dimenzije (VxŠxD)	848x578x629 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	310x250x340 mm
Firebox dimensions (HxWxD)	
Snaga	6,8 kW
Power	
Stepen iskorišćenja	78,1 %
Efficiency	
Odvod dima	pozadi /
Fume outlet	rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



OLYMP II S

Dimenzije (VxŠxD)	848x578x629 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	310x250x340 mm
Firebox dimensions (HxWxD)	
Snaga	6,8 kW
Power	
Stepen iskorišćenja	78,1 %
Efficiency	
Odvod dima	pozadi /
Fume outlet	rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



OLYMPIA II

Dimenzije (VxŠxD)	1120x578x629 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	310x250x340 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	280x270x420 mm
Oven dimensions (HxWxD)	
Snaga	8,5 kW
Power	
Stepen iskorišćenja	83,7 %
Efficiency	
Odvod dima	pozadi /
Fume outlet	rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



OLYMPIA II S

Dimenzije (VxŠxD)	1120x578x629 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	310x250x340 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	280x270x420 mm
Oven dimensions (HxWxD)	
Snaga	8,5 kW
Power	
Stepen iskorišćenja	83,7 %
Efficiency	
Odvod dima	pozadi /
Fume outlet	rear / Ø 120 mm
Tip goriva	drvo
Fuel type	wood



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



VULKAN II

Dimenzije (VxŠxD)	750x650x531 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	265x390x400 mm
Firebox dimensions (HxWxD)	
Snaga	8,2 kW
Power	
Stepen iskorišćenja	75,3 %
Efficiency	
Odvod dima	gore /
Fume outlet	top / Ø 150 mm
Tip goriva	drvo
Fuel type	wood

EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



SD EVA

Dimenzije (VxŠxD)	780x608x550 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	400x500x420 mm
Firebox dimensions (HxWxD)	
Snaga	8,2 kW
Power	
Stepen iskorišćenja	76,9 %
Efficiency	
Odvod dima	gore /
Fume outlet	top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood





SD EVA PLUS

Dimenzije (VxŠxD)	930x608x550 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	400x500x420 mm
Firebox dimensions (HxWxD)	
Snaga	8,2 kW
Power	
Stepen iskorišćenja	76,9 %
Efficiency	
Odvod dima	gore /
Fume outlet	top / Ø 120 mm
Tip goriva	drvo
Fuel type	wood

Štednjaci i peći za etažno grejanje

Central heating cookers and stoves



SD THERMO MAGNUM

Dimenzije (VxŠxD)	860x1075x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	300x250x340 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	270x350x470 mm
Oven dimensions (HxWxD)	
Snaga (drvo)	14,3 kW
Power (wood)	
Snaga predana vodi (drvo)	10,2 kW
Power given to water (wood)	
Snaga predana okolini (drvo)	4,1kW
Power given to room (wood)	
Zapremina kotla	11 l
Boiler volume	
Stepen iskorišćenja (drvo)	76,4 %
Efficiency (wood)	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 150 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





SD THERMO MAGNUM S

Dimenzije (VxŠxD) Dimensions (HxWxD)	860x1075x660 mm
Dimenzije ložišta (VxŠxD) Firebox dimensions (HxWxD)	300x250x340 mm
Dimenzije pećnice (VxŠxD) Oven dimensions (HxWxD)	270x350x470 mm
Snaga (drvo) Power (wood)	14,3 kW
Snaga predata vodi (drvo) Power given to water (wood)	10,2 kW
Snaga predata okolini (drvo) Power given to room (wood)	4,1kW
Zapremina kotla Boiler volume	11 l
Stepen iskorišćenja (drvo) Efficiency (wood)	76,4 %
Odvod dima Fume outlet	gore, pozadi / top, rear / Ø 150 mm
Tip goriva Fuel type	drvo wood

SD SUPER THERMO MAGNUM

Dimenzije (VxŠxD)	865x1075x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	265x400x428 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	280x270x420 mm
Oven dimensions (HxWxD)	
Snaga	16,3 kW
Power	
Snaga predata vodi	10,1 kW
Power given to water	
Snaga predata okolin	6,2 kW
Power given to room	
Zapremina kotla	19 l
Boiler volume	
Stepen iskorišćenja	77,5 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 130 / 150 mm
Tip goriva	drvo
Fuel type	wood

Boje
Colors





SD SUPER THERMO MAGNUM S

Dimenzije (VxŠxD)	865x1075x660 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	265x400x428 mm
Firebox dimensions (HxWxD)	
Dimenzije pećnice (VxŠxD)	280x270x420 mm
Oven dimensions (HxWxD)	
Snaga	16,3 kW
Power	
Snaga predata vodi	10,1 kW
Power given to water	
Snaga predata okolin	6,2 kW
Power given to room	
Zapremina kotla	19 l
Boiler volume	
Stepen iskorišćenja	77,5 %
Efficiency	
Odvod dima	gore, pozadi /
Fume outlet	top, rear / Ø 130 / 150 mm
Tip goriva	drvo
Fuel type	wood

SD THERMO VESTA PLUS

Dimenzije (VxŠxD)	890x455x440 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	410x215x335 mm
Firebox dimensions (HxWxD)	
Snaga (drvo / ugalj)	11,2 kW
Power (wood / coal)	
Snaga predata vodi (drvo / ugalj)	7,1 kW
Power given to water (wood / coal)	
Snaga predata okolini (drvo / ugalj)	4,1 kW
Power given to room (wood / coal)	
Zapremina kotla	4 l
Boiler volume	
Stepen iskorišćenja (drvo / ugalj)	77 %
Efficiency (wood / coal)	
Odvod dima	gore /
Fume outlet	top / Ø 120 mm
Tip goriva (drvo / ugalj)	drvo
Fuel type (wood / coal)	wood

Boje
Colors





SD THERMO VULKAN

Dimenzije (VxŠxD) Dimensions (HxWxD)	808x650x545 mm
Dimenzije ložišta (VxŠxD) Firebox dimensions (HxWxD)	320x405x400 mm
Snaga Power	18,4 kW
Snaga predata vodi Power given to water	13,2 kW
Snaga predata okolini Power given to room	5,2 kW
Zapremina kotla Boiler volume	24 l
Stepen iskorišćenja Efficiency	77,1 %
Odvod dima Fume outlet	gore / top / Ø 150 mm
Tip goriva Fuel type	drvo wood

SD THERMO VULKAN S

Dimenzije (VxŠxD) Dimensions (HxWxD)	808x650x545 mm
Dimenzije ložišta (VxŠxD) Firebox dimensions (HxWxD)	320x405x400 mm
Snaga Power	18,4 kW
Snaga predana vodi Power given to water	13,2 kW
Snaga predana okolini Power given to room	5,2 kW
Zapremina kotla Boiler volume	24 l
Stepen iskorišćenja Efficiency	77,1 %
Odvod dima Fume outlet	gore / top / Ø 150 mm
Tip goriva Fuel type	drvo wood



SD THERMO VULKAN PLUS



Dimenzije (VxŠxD) Dimensions (HxWxD)	1170x650x556 mm
Dimenzije ložišta (VxŠxD) Firebox dimensions (HxWxD)	290x425x400 mm
Dimenzije pećnice (VxŠxD) Oven dimensions (HxWxD)	270x350x470 mm
Snaga (drvo / ugalj) Power (wood / coal)	18,4 kW
Snaga predata vodi (drvo / ugalj) Power given to water (wood / coal)	15,2 kW
Snaga predata okolini (drvo / ugalj) Power given to room (wood / coal)	3,2 kW
Zapremina kotla Boiler volume	18 l
Stepen iskorišćenja (drvo / ugalj) Efficiency (wood / coal)	77,6 %
Odvod dima Fume outlet	gore / top / Ø 150 mm
Tip goriva Fuel type	drvo wood

SD THERMO IN

Dimenzije (VxŠxD)	1000x650x545 mm
Dimensions (HxWxD)	
Dimenzije ložišta (VxŠxD)	390x410x370 mm
Firebox dimensions (HxWxD)	
Snaga (drvo)	19,5 kW
Power (wood)	
Snaga predana vodi (drvo)	16 kW
Power given to water (wood)	
Snaga predana okolini (drvo)	3,5 kW
Power given to room (wood)	
Zapremina kotla	23 l
Boiler volume	
Stepen iskorišćenja (drvo)	77,2 %
Efficiency (wood)	
Odvod dima	gore /
Fume outlet	top / Ø 150 mm
Tip goriva (drvo)	drvo
Fuel type (wood)	wood



Peći, štednjaci i kotlovi na pellet

Pellet stoves, cookers and boilers



SD PELLET ECO

Dimenzije (VxŠxD) Dimensions (HxWxD)	980x560x490 mm
--	----------------

Snaga (min-max) Power (min-max)	2,98 kW - 6,22 kW
---	-------------------

Snaga električnog dela Power of electric part	0,5 kW
---	--------

Stepen iskorišćenja * Efficiency *	89,87 % / 89,21 %
--	-------------------

Odvod dima Fume outlet	zadnji / back / Ø 80 mm
----------------------------------	-----------------------------------

Tip goriva Fuel type	pelet pellet
--------------------------------	------------------------

Nedeljno programiranje rada (do sedam dana unapred) /
Automatsko puštanje u rad / Daljinsko upravljanje
Weekly programming (up to seven days in advance) /
Automatic start-up / Remote control

* pri minimalnoj snazi / pri maksimalnoj snazi

* **at minimal power / at maximal power**

Boje
Colors



HELLIA



Dimenzije (VxŠxD) Dimensions (HxWxD)	1000x520x560 mm
Snaga (min-max) Power (min-max)	3,85 kW - 8,11 kW
Snaga električnog dela Power of electric part	0,5 kW
Stepen iskorišćenja * Efficiency *	93,05 % / 91,92 %
Odvod dima Fume outlet	zadnji / back / Ø 80 mm
Tip goriva Fuel type	pelet pellet
Nedeljno programiranje rada (do sedam dana unapred) / Automatsko puštanje u rad / Daljinsko upravljanje Weekly programming (up to seven days in advance) / Automatic start-up / Remote control	
* pri minimalnoj snazi / pri maksimalnoj snazi * at minimal power / at maximal power	



SD THERMO PELLET

Dimenzije (VxŠxD) Dimensions (HxWxD)	1232x604x788 mm
Snaga (min-max) Power (min-max)	6,9 kW - 16,0 kW
Snaga predata vodi (min-max) Power given to water (min-max)	5,0 kW - 11,6 kW
Snaga predata okolini (min-max) Power given to room (min-max)	1,9 kW - 4,4 kW
Snaga električnog dela Power of electric part	0,5 kW
Zapremina kotla Boiler volume	46 l
Stepen iskorišćenja * Efficiency *	94,19 % / 90,68 %
Odvod dima Fume outlet	zadnji / back / Ø 80 mm
Tip goriva Fuel type	pelet pellet
Nedeljno programiranje rada (do sedam dana unapred) / Automatsko puštanje u rad / Daljinsko upravljanje Weekly programming (up to seven days in advance) / Automatic start-up / Remote control	

* pri minimalnoj snazi / pri maksimalnoj snazi

* at minimal power / at maximal power

Boje / Colors



EN 16510

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025





SD STRONG PELLET

Dimenzije (VxŠxD) Dimensions (HxWxD)	875x900x655 mm
Dimenzije pećnice (VxŠxD) Oven dimensions (HxWxD)	346x300x440 mm
Snaga (min - max) Power (min - max)	6,4 kW - 10,8 kW
Stepen iskorišćenja * Efficiency *	95,19 % / 90,558 %
Odvod dima Fume outlet	gornji / up / Ø 120 mm
Tip goriva Fuel type	pellet pellet
Nedeljno programiranje rada (do sedam dana unapred) / Automatsko puštanje u rad / Daljinsko upravljanje Weekly programming (up to seven days in advance) / Automatic start-up / Remote control	
* pri minimalnoj snazi / pri maksimalnoj snazi * at minimal power / at maximal power	



Boje
Colors

ECO PELLET S

Dimenzije (VxŠxD)	1235x604x856 mm
Dimensions (HxWxD)	
Snaga (min-max)	5,22 kW - 15,48 kW
Power (min-max)	
Snaga električnog dela	527 W
Power of electric part	
Zapremina kotla	42 l
Boiler volume	
Stepen iskorišćenja *	87,6 % / 88,67 %
Efficiency *	
Odvod dima	zadnji /
Fume outlet	back / Ø 80 mm
Tip goriva	pelet
Fuel type	pellet

Nedeljno programiranje rada (do sedam dana unapred) /
Automatsko puštanje u rad / Daljinsko upravljanje
Weekly programming (up to seven days in advance) /
Automatic start-up / Remote control

* pri minimalnoj snazi / pri maksimalnoj snazi

* at minimal power / at maximal power



EN 3033-5:2021

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025



ECO PELLET M



EN 3033-5:2021

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025

Dimenzije (VxŠxD) Dimensions (HxWxD)	1345x644x867 mm
Snaga (min-max) Power (min-max)	6,55 kW - 24,57 kW
Snaga električnog dela Power of electric part	613 W
Zapremina kotla Boiler volume	48 l
Stepen iskorišćenja * Efficiency *	89,73 % / 89,45 %
Odvod dima Fume outlet	zadnji / back / Ø 100 mm
Tip goriva Fuel type	pelet pellet

Nedeljno programiranje rada (do sedam dana unapred) /
Automatsko puštanje u rad / Daljinsko upravljanje
Weekly programming (up to seven days in advance) /
Automatic start-up / Remote control

* pri minimalnoj snazi / pri maksimalnoj snazi

* **at minimal power / at maximal power**

ECO PELLET 33

Dimenzije (VxŠxD)	1455x714x988 mm
Dimensions (HxWxD)	
Snaga (min-max)	9,93 kW - 32,05 kW
Power (min-max)	
Snaga električnog dela	0,534 kW
Power of electric part	
Zapremina kotla	76 l
Boiler volume	
Stepen iskorišćenja *	90,25 % / 90,95 %
Efficiency *	
Odvod dima	zadnji /
Fume outlet	back / Ø 120 mm
Tip goriva	pelet
Fuel type	pellet

Nedeljno programiranje rada (do sedam dana unapred) /
Automatsko puštanje u rad / Daljinsko upravljanje
Weekly programming (up to seven days in advance) /
Automatic start-up / Remote control

* pri minimalnoj snazi / pri maksimalnoj snazi

* at minimal power / at maximal power



EN 3033-5:2021

EUROPEAN
STANDARDS

FOR RESIDENTIAL
SOLID FUEL BURNING
APPLIANCES

2025

Električni stoni štednjak

Electric tabletop cooker



MINI

Dimenzije (VxŠxD) Dimensions (HxWxD)	315x570x350 mm
Ukupna instalisana snaga Total installed power	3,6 kW
●○ Ringla - standardna Hot plate - standard	Ø145mm/1,0 kW
○● Ringla - standardna Hot plate - standard	Ø180mm/1,5 kW
Dimenzije pećnice (VxŠxD) Oven dimensions (HxWxD)	205x367x325 mm
Zapremina pećnice / Oven volume	23 l
Gornji grejač / Upper heater	550 W
Donji grejač / Bottom heater	550 W
Maksimalna temperatura pećnice / Max oven temperature	250°C
Emajlirana tava / Enamelled frying pan	•
Rešetka / Grid	•
Vrata sa dvostrukim staklom / Double glass door	•
Energetska efikasnost / Energy efficiency class	A

Boje
Colors



Tabela tehničkih karakteristika

Technical data table



MODEL / MODEL	SD 3	SD 7 SL	SD 7 RS	SD 9 SL	SD 9 RS
Dimenzije (VxŠxD) / Dimensions (HxWxD)	740x720x570 mm	740x820x645 mm	740x820x645 mm	740x945x645 mm	740x945x645 mm
Dimenzije ložišta (VxŠxD) / Firebox dimensions (HxWxD)	195x200x300 mm	250x200x400 mm	250x200x400 mm	250x200x400 mm	250x200x400 mm
Dimenzije pećnice (VxŠxD) / Oven dimensions (HxWxD)	200x300x400 mm	200x430x460 mm	200x430x460 mm	200x490x460 mm	200x490x460 mm
Snaga / Power	7 kW	7 kW	7 kW	7 kW	7 kW
Snaga predata vodi / Power given to water					
Snaga predata okolini / Power given to room					
Stepen iskorišćenja / Efficiency	75 %	75 %	75 %	75 %	75 %
Emisija CO / The average CO value	1430 mg/Nm ³	1430 mg/Nm ³	1430 mg/Nm ³	1430 mg/Nm ³	1430 mg/Nm ³
Emisija prašine / Dust	32 mg/Nm ³	32 mg/Nm ³	32 mg/Nm ³	32 mg/Nm ³	32 mg/Nm ³
Zapremina kotla / Boiler volume					
Priključak odvoda dima / Fume outlet position	sa strane / side	sa strane / side	sa strane / side	sa strane / side	sa strane / side
Prečnik priključka odvoda dima / Fume outlet diameter	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm
Temperatura izduvnih gasova / Smoke temperature	258 °C	258 °C	258 °C	258 °C	258 °C
Težina / Weight	70 kg	83 kg	84 kg	89 kg	91 kg
Tip goriva / Fuel type	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
Potrošnja goriva / Fuel consumption	1,84 kg/h	1,84 kg/h	1,84 kg/h	1,84 kg/h	1,84 kg/h
Kapacitet grejanja (maksimalno) / Heatable volume (max)	46 m ²	46 m ²	46 m ²	46 m ²	46 m ²



SD 10	SD Trend	Royal 720 2.0	King	Ares / Ares Lux	AS II	AS II S	Magnum II
850x945x645 mm	855x900x495 mm	850x720x600 mm	860-900x810x600 mm	860-900x810x600 mm	845x900x654 mm	845x900x654 mm	850x1070x660 mm
250x200x400 mm	270x335x370 mm	175x250x400 mm	270x197x345 mm	300x197x385 mm	270x270x350 mm	270x270x350 mm	300x250x340 mm
200x490x460 mm	205x370x325 mm	270x350x470 mm	270x350x470 mm	270x350x470 mm	270x350x470 mm	270x350x470 mm	270x350x470 mm
7 kW	7,1 kW	6,5 kW	7,8 kW	7,37 kW	9,9 kW	9,9 kW	7,75 kW
75 %	76,3 %	83,6 %	75,4 %	78,4 %	82 %	82 %	83,8 %
1431 mg/Nm ³	1076,25 mg/Nm ³	1165 mg/Nm ³	962 mg/Nm ³	1127 mg/Nm ³	855 mg/Nm ³	855 mg/Nm ³	1419 mg/Nm ³
32 mg/Nm ³	27 mg/Nm ³	27,7 mg/Nm ³	38 mg/Nm ³	34 mg/Nm ³	38 mg/Nm ³	38 mg/Nm ³	37 mg/Nm ³
sa strane, gore / side, top	sa strane / side	gore, pozadi / top, rear	sa strane, gore, pozadi / side, top, rear	sa strane, gore / side, top	gore, pozadi / top, rear	gore, pozadi / top, rear	gore, pozadi / top, rear
Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm
258 °C	285 °C	143 °C	166 °C	172 °C	176 °C	176 °C	169 °C
106 kg	93 kg	121 kg	140 kg	139 kg	155 kg	180 kg	164 kg
drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
1,84 kg/h	1,9 kg/h	1,82 kg/h	2,24 kg/h	2,129 kg/h	2,7 kg/h	2,7 kg/h	2,225 kg/h
46 m ²	46 m ²	42 m ²	51,5 m ²	48 m ²	54 m ²	54 m ²	50 m ²



MODEL / MODEL	Magnum II S	Grand 90	SD Strong	SD Happy Eco	SD Hera
Dimenzije (VxŠxD) / Dimensions (HxWxD)	850x1070x660 mm	870-900x900x600 mm	865x915x655 mm	712x400x406 mm	850x400x560 mm
Dimenzije ložišta (VxŠxD) / Firebox dimensions (HxWxD)	300x250x340 mm	250x210x456 mm	195x200x400 mm	247x282x293 mm	350x290x300 mm
Dimenzije pećnice (VxŠxD) / Oven dimensions (HxWxD)	270x350x470 mm	248x302x420 mm	440x300x445 mm		
Snaga / Power	7,75 kW	7 kW	7,6 kW	5,7 kW	6,2 kW
Snaga predata vodi / Power given to water					
Snaga predata okolini / Power given to room					
Stepen iskorišćenja / Efficiency	83,8 %	73,2 %	76,5 %	80,9 %	76,4 %
Emisija CO / The average CO value	1419 mg/Nm ³	0,077 %	1191 mg/Nm ³	1208 mg/Nm ³	1221,25 mg/Nm ³
Emisija prašine / Dust	37 mg/Nm ³	0,031 g/m ³	32 mg/Nm ³	36 mg/Nm ³	29 mg/Nm ³
Zapremina kotla / Boiler volume					
Priključak odvoda dima / Fume outlet position	gore, pozadi / top, rear	sa strane, gore, pozadi / side, top, rear	gore, pozadi / top, rear	gore / top	gore / top
Prečnik priključka odvoda dima / Fume outlet diameter	Ø 120 mm	Ø 120 mm	Ø 120 / 130 mm	Ø 120 mm	Ø 120 mm
Temperatura izduvnih gasova / Smoke temperature	169 °C	242 °C	222 °C	180 °C	290 °C
Težina / Weight	205,5 kg	170 kg	222 kg	54 kg	89 kg
Tip goriva / Fuel type	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
Potrošnja goriva / Fuel consumption	2,225 kg/h	2,5 kg/h	2,03 kg/h	1,73 kg/h	1,65 kg/h
Kapacitet grejanja (maksimalno) / Heatable volume (max)	50 m ²	45,5 m ²	49,5 m ²	37 m ²	40 m ²



SD Hit Eco	SD Corner Eco	Luna	Orion	Vega	SD Vesta Eco	Vesta Plus II	Elit II
850x504x440 mm	850x635x575 mm	989x518x410 mm	1010x518x411 mm	1044x493x431 mm	890x455x440 mm	940x455x440 mm	985x588x493 mm
260x252x290 mm	260x252x290 mm	265x320x279 mm	265x320x279 mm	293x335x310 mm	400x280x340 mm	390x250x350 mm	298x400x364 mm
6,4 kW	6,3 kW	6 kW	6 kW	6,4 kW	8,2 kW	7,5 kW	7,8 kW
81,6 %	78 %	80 %	80 %	80 %	77,8 %	85,1 %	85,1 %
1215 mg/Nm ³	821 mg/Nm ³	0,097 %	0,097 %	1148 mg/Nm ³	942,5 mg/Nm ³	859 mg/Nm ³	1002 mg/Nm ³
35 mg/Nm ³	37 mg/Nm ³	38 mg/Nm ³	0,038 g/m ³	32 mg/Nm ³	30 mg/Nm ³	27 mg/Nm ³	31 mg/Nm ³
gore / top	gore / top	gore / top	gore / top	gore / top	gore / top	gore / top	gore / top
Ø 120 mm	Ø 120 mm	Ø 150 mm	Ø 150 mm	Ø 150 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm
197 °C	238 °C	231 °C	231 °C	219 °C	287 °C	181 °C	197 °C
70 kg	70 kg	100 kg	100 kg	144 kg	78 kg	87 kg	124 kg
drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
1,89 kg/h	1,98 kg/h	1,3 kg/h / ---	1,3 kg/h / ---	1,6 kg/h	2,15 kg/h	2,12 kg/h	2,2 kg/h
41,5 m ²	41 m ²	39 m ²	39 m ²	41,5 m ²	53 m ²	49 m ²	51 m ²

TABELA TEHNIČKIH PODATAKA / drvo
TECHNICAL DATA TABLE / wood



MODEL / MODEL	Aria / Aria Lux	Grand 50	Olymp II	Olymp II S	Olympia II
Dimenzije (VxŠxD) / Dimensions (HxWxD)	845x434x660 mm	860-900x515x573 mm	848x578x629 mm	848x578x629 mm	1120x578x629 mm
Dimenzije ložišta (VxŠxD) / Firebox dimensions (HxWxD)	414x250x340 mm	256x381x375 mm	310x250x340 mm	310x250x340 mm	310x250x340 mm
Dimenzije pećnice (VxŠxD) / Oven dimensions (HxWxD)					280x270x420 mm
Snaga / Power	8 kW	7 kW	6,8 kW	6,8 kW	8,5 kW
Snaga predata vodi / Power given to water					
Snaga predata okolini / Power given to room					
Stepen iskorišćenja / Efficiency	77 %	76,3 %	78,1 %	78,1 %	83,7 %
Emisija CO / The average CO value	1151 mg/Nm ³	0,087 %	1137 mg/Nm ³	1137 mg/Nm ³	1399 mg/Nm ³
Emisija prašine / Dust	37 mg/Nm ³	0,034 g/m ³	36 mg/Nm ³	36 mg/Nm ³	37 mg/Nm ³
Zapremina kotla / Boiler volume					
Priključak odvoda dima / Fume outlet position	gore, pozadi / top, rear	gore / top	pozadi / rear	pozadi / rear	pozadi / rear
Prečnik priključka odvoda dima / Fume outlet diameter	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm	Ø 120 mm
Temperatura izduvnih gasova / Smoke temperature	210 °C	258 °C	195 °C	195 °C	167 °C
Težina / Weight	80 kg	125 kg	110 kg	131 kg	161 kg
Tip goriva / Fuel type	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
Potrošnja goriva / Fuel consumption	2,37 kg/h	2,5 kg/h	2,087 kg/h	2,087 kg/h	2,45 kg/h
Kapacitet grejanja (maksimalno) / Heatable volume (max)	52 m ²	45,5 m ²	44 m ²	44 m ²	55 m ²



Olympia II S	Vulkan II	SD Eva	SD Eva Plus	SD Thermo Magnum	SD Thermo Magnum S	SD Super Thermo Magnum	SD Super Thermo Magnum S
1120x578x629 mm	750x650x531 mm	780x608x550 mm	930x608x550 mm	860x1075x660 mm	860x1075x660 mm	860x1075x660 mm	860x1075x660 mm
310x250x340 mm	265x390x400 mm	400x500x420 mm	400x500x420 mm	300x250x340 mm	300x250x340 mm	265x400x428 mm	265x400x428 mm
280x270x420 mm				270x350x470 mm	270x350x470 mm	280x270x420 mm	280x270x420 mm
8,5 kW	8,2 kW	8,2 Kw	8,2 Kw	14,3 kW	14,3 kW	16,3 kW	16,3 kW
				10,2 kW	10,2 kW	10,1 kW	10,1 kW
				4,1 kW	4,1 kW	6,2 kW	6,2 kW
83,7 %	75,3 %	76,9 %	76,9 %	76,4 %	76,4 %	77,5 %	77,5 %
1399 mg/Nm ³	1163 mg/Nm ³	1181,25 mg/Nm ³	1181,25 mg/Nm ³	1006,25 mg/Nm ³	1006,25 mg/Nm ³	1172,5 mg/Nm ³	1172,5 mg/Nm ³
37 mg/Nm ³	36 mg/Nm ³	29 mg/Nm ³	29 mg/Nm ³	33 mg/Nm ³	33 mg/Nm ³	37 mg/Nm ³	37 mg/Nm ³
				11 l	11 l	19 l	19 l
pozadi / rear	gore / top	gore / top	gore / top	gore, pozadi / top, rear	gore, pozadi / top, rear	gore, pozadi / top, rear	gore, pozadi / top, rear
Ø 120 mm	Ø 150 mm	Ø 120 mm	Ø 120 mm	Ø 150 mm	Ø 150 mm	Ø 130 / 150 mm	Ø 130 / 150 mm
167 °C	244 °C	284 °C	284 °C	285 °C	285 °C	286 °C	286 °C
185 kg	186 kg	141 kg	157 kg	175 kg	211 kg	187 kg	219 kg
drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
2,45 kg/h	2,6 kg/h	2,2 kg/h	2,2 kg/h	3,68 kg/h	3,68 kg/h	4,13 kg/h	4,13 kg/h
55,5 m ²	53 m ²	53 m ²	53 m ²	93 m ²	93 m ²	106 m ²	106 m ²



MODEL / MODEL	SD Thermo Vesta Plus	SD Thermo Vulkan	SD Thermo Vulkan S	SD Thermo Vulkan Plus	SD Thermo In
Dimenzije (VxŠxD) / Dimensions (HxWxD)	890x455x440 mm	808x650x545 mm	808x650x545 mm	1170x650x556 mm	1000x650x545 mm
Dimenzije ložišta (VxŠxD) / Firebox dimensions (HxWxD)	410x215x335 mm	320x405x400 mm	320x405x400 mm	290x425x400 mm	390x410x370 mm
Dimenzije pećnice (VxŠxD) / Oven dimensions (HxWxD)				270x350x470 mm	
Snaga / Power	11,2 kW	18,4 kW	18,4 kW	18,4 kW	19,5 kW
Snaga predata vodi / Power given to water	7,1 kW	13,2 kW	13,2 kW	15,2 kW	16 kW
Snaga predata okolini / Power given to room	4,1 kW	5,2 kW	5,2 kW	3,2 kW	3,5 kW
Stepen iskorišćenja / Efficiency	77 %	77,1 %	77,1 %	77,6 %	77,2 %
Emisija CO / The average CO value	1057 mg/Nm ³	882,5 mg/Nm ³	882,5 mg/Nm ³	902,5 mg/Nm ³	1141 mg/Nm ³
Emisija prašine / Dust	28 mg/Nm ³	36 mg/Nm ³	36 mg/Nm ³	29 mg/Nm ³	28 mg/Nm ³
Zapremina kotla / Boiler volume	4 l	24 l	24 l	18 l	23 l
Priključak odvoda dima / Fume outlet position	gore / top	gore / top	gore / top	gore / top	gore / top
Prečnik priključka odvoda dima / Fume outlet diameter	Ø 120 mm	Ø 150 mm	Ø 150 mm	Ø 150 mm	Ø 150 mm
Temperatura izduvnih gasova / Smoke temperature	290 °C	297 °C	297 °C	307 °C	280 °C
Težina / Weight	95 kg	152 kg	184 kg	235 kg	166,5 kg
Tip goriva / Fuel type	drvo / wood	drvo / wood	drvo / wood	drvo / wood	drvo / wood
Potrošnja goriva / Fuel consumption	2,98 kg/h	4,67 kg/h	4,67 kg/h	4,84 kg/h	5,2 kg/h
Kapacitet grejanja (maksimalno) / Heatable volume (max)	73 m ²	120 m ²	120 m ²	120 m ²	126 m ²



MODEL / MODEL	SD Pellet Eco	Hellia	SD Thermo Pellet	SD Strong pellet
Dimenzije (VxŠxD) / Dimensions (HxWxD)	980x560x490 mm	1000x520x560 mm	1232x604x788 mm	875x900x655 mm
Dimenzije ložišta (VxŠxD) / Firebox dimensions (HxWxD)	/	/	/	/
Dimenzije pećnice (VxŠxD) / Oven dimensions (HxWxD)	/	/	/	346x300x440 mm
Snaga (min-max) / Power (min-max)	2,98 kW - 6,22 kW	3,85 kW - 8,11 kW	6,9 kW - 16,0 kW	6,4 kW - 10,08 kW
Snaga predata vodi (min-max) / Power given to water (min-max)	/	/	5,0 kW - 11,6 kW	/
Snaga predata okolini (min-max) / Power given to room (min-max)	/	/	1,9 kW - 4,4 kW	/
Stepen iskorišćenja * / Efficiency *	89,87 % / 89,21 %	93,05 % / 91,92 %	94,19 % / 90,68 %	95,19 % / 90,558 %
Emisija CO - svedeno na 13% O ₂ * The average CO value - at 13% O ₂ *	139 mg/Nm ³ / 190 mg/Nm ³	138 mg/Nm ³ / 31 mg/Nm ³	250 mg/Nm ³ / 259 mg/Nm ³	236 mg/Nm ³ / 188 mg/Nm ³
Emisija prašine - svedeno na 13% O ₂ * / Dust - at 13% O ₂ *	17,8 mg/Nm ³ / 17,6 mg/Nm ³	19,7 mg/Nm ³ / 19,5 mg/Nm ³	17,6 mg/Nm ³ / 16,8 mg/Nm ³	18,2 mg/Nm ³ / 18,1 mg/Nm ³
Zapremina kotla / Boiler volume	/	/	46 l	/
Priključak odvoda dima / Fume outlet position	pozadi / rear	pozadi / rear	pozadi / rear	gore / top
Prečnik priključka odvoda dima / Fume outlet diameter	Ø 80 mm	Ø 80 mm	Ø 80 mm	Ø 120 mm
Temperatura izduvnih gasova * / Smoke temperature *	90 °C / 124,5 °C	79 °C / 117 °C	61 °C / 114 °C	75 °C / 127 °C
Težina / Weight	102 kg	120 kg	177 kg	210 kg
Tip goriva / Fuel type	pelet / pellet	pelet / pellet	pelet / pellet	pelet / pellet
Potrošnja goriva * / Fuel consumption *	0,667 kg/h / 1,4 kg/h	0,87 kg/h / 1,858 kg/h	1,467 kg/h / 3,533 kg/h	1,35 / 2,23 kg/h
Kapacitet grejanja (maksimalno) / Heatable volume (max)	40,5 m ²	52,5 m ²	104 m ²	66,5 m ²
Kapacitet spremnika za pelet ** / Pellet tank capacity **	15 kg	15 kg	20 kg	15 kg

* pri minimalnoj snazi / pri maksimalnoj snazi / at minimal power / at maximal power

** zavisno od dimenzija peleta / depending on pellet dimensions



MODEL / MODEL	Eco Pellet S	Eco Pellet M	Eco Pellet 33
Dimenzije (VxŠxD) / Dimensions (HxWxD)	1235x604x856 mm	1345x644x867 mm	1455x714x988 mm
Dimenzije ložišta (VxŠxD) / Firebox dimensions (HxWxD)			
Dimenzije pećnice (VxŠxD) / Oven dimensions (HxWxD)			
Snaga (min-max) / Power (min-max)	5,22 kW - 15,48 kW	6,55 kW - 24,57 kW	9,93 kW - 32,05 kW
Snaga predana vodi (min-max) / Power given to water (min-max)			
Snaga predana okolini (min-max) / Power given to room (min-max)			
Stepen iskorišćenja * / Efficiency *	87,6 % / 88,67 %	89,73 % / 89,45 %	90,25 % / 90,95 %
Emisija CO - svedeno na 10% O ₂ *	151 mg/Nm ³ / 339 mg/Nm ³	103 mg/Nm ³ / 60 mg/Nm ³	398 mg/Nm ³ / 117 mg/Nm ³
The average CO value - at 10% O ₂ *			
Emisija prašine - svedeno na 10% O ₂ * / Dust - at 10% O ₂ *	35,4 mg/Nm ³ / 25,5 mg/Nm ³	37 mg/Nm ³ / 31,8 mg/Nm ³	26,8 mg/Nm ³ / 29,6 mg/Nm ³
Zapremina kotla / Boiler volume	42 l	48 l	76 l
Priključak odvoda dima / Fume outlet position	pozadi / rear	pozadi / rear	pozadi / rear
Prečnik priključka odvoda dima / Fume outlet diameter	Ø 80 mm	Ø 100 mm	Ø 120 mm
Temperatura izduvnih gasova * / Smoke temperature *	61 °C / 114 °C	56 °C / 114 °C	70 °C - 120 °C
Težina / Weight	320 kg	325 kg	370 kg
Tip goriva / Fuel type	pelet / pellet	pelet / pellet	pelet / pellet
Potrošnja goriva * / Fuel consumption *	1,467 kg/h / 3,533 kg/h	1,5 kg/h / 5,75 kg/h	1,7 kg/h / 7,3 kg/h
Kapacitet grejanja (maksimalno) / Heatable volume (max)	100,5 m ²	160 m ²	214,5 m ²
Kapacitet spremnika za pelet ** / Pellet tank capacity **	40 kg	70 kg	70 kg

* pri minimalnoj snazi / pri maksimalnoj snazi / at minimal power / at maximal power

** zaviso od dimenzija peleta / depending on pellet dimensions



Smederevac d.o.o.

Đure Strugara 20
11300 Smederevo
Srbija
tel: 026 633 601
e-mail: office@smederevac.com

•

Djуре Strugara 20
11300 Smederevo
Serbia
tel: +381 26 633 601
e-mail: office@smederevac.com

www.smederevac.com